



RECOMMENDED PCB LAYOUT  
TOLERANCE ±0.05

Specification:  
 \*Electrical Characteristics:  
 Contact Current Rating:0.5 Amperes  
 Dielectric Withstanding Voltage:AC500V r.m.s  
 Insulation Resistance:5000M Minimum  
 Contact Resistance:300m Maximum  
 \*Environmental:  
 Operating Temperature:-55°C~+85°C  
 Mating Cycles:5000 Insertions  
 \*Material:  
 Insulator:HI-Temp Plastic UL94v-0 Rated  
 Contact:Copper Alloy  
 Shell:SUS

TYPE	"A"	Part NO
H=1.8mm	1.8mm	JYS-SIM180-104
H=1.5mm	1.5mm	JYS-SIM150-106

GENERAL TOLERANCE		DWG NO.	JYS40525-009	APPD:	WMD	Scale
X±0.45	X:±5'	Title	SIM CARD 6PIN 连接器 (防浪PIN)	CHKD:		1:1
X±0.35	X:±2'	Part NO.	SEE TABLE	DR:		mm
.XX±0.25	.XX'±1'			Date	2015/11/29	
.XXX±0.15	.xxx'±0.5'					
SHEET 1/1						



REV.	EQN.NO.	MODIFY CONTENT	DATE
A		NEW	2015/11/29